WRR-5301/5301L

Wisenet WAVE Network Video Recorder



WRR-5301 series servers are Wisenet WAVE optimized 2U rackmounted Network Video Recorders capable of recording up to 470Mbps, managing up to 64TB of storage, and available in both Windows 10 IoT and Linux Ubuntu OS.

Each is pre-configured with Wisenet WAVE VMS and preloaded with 4 Professional licenses to ensure quick and easy deployment with minimum setup time.

Key Features

- Preloaded and configured with Wisenet WAVE video management system
- Includes (4) four Wisenet WAVE Professional licenses
- 470 Mbps of recording throughput
- Up to 64TB internal storage
- Redundant 800W power supply
- Includes USB mouse and keyboard
- Includes a sliding rail kit
- Includes front bezel with lock
- Supports Wisenet and ONVIF conformant IP cameras
- Available in Windows 10 IoT Enterprise and Linux Ubuntu 16.04 LTS

100 to 10	
	VSPC WA
	M Comments
R CONTRACTOR OF THE PARTY OF TH	-

	WRR-5301	WRR-5301L		
SYSTEM				
Video Management Software	Wisenet WAVE			
Pre-loaded Licenses	4x Wisenet WAVE Professional license			
Recording Bandwidth	Up to 470 Mbps			
OS Drive Bays	1 x 256GB SSD (internally mounted)			
Data Drive Bays	8 x 3.5" HDD			
Data Storage	Up to 64TB raw			
RAID Support	N/A			
Network Interface	2 x RJ-45, Gigabit Ethernet			
Processor	Intel Core i5-7500, 3.4GHz			
Memory	8GB DDR4			
Operating System	Windows 10 IoT Enterprise	Linux Ubuntu 16.04 LTS		
Video Outputs	1x Display Port (rear), 1x HDMI (rear), 1x DVI (rear)			
USB Ports	6x USB 3.0 (rear), 1x USB 3.0 (front)			
Other Ports	3.5mm audio in/out, 1x SPDIF out			
Keyboard & Mouse	Included			
Sliding Rail Kit	Included			

MECHANICAL / ELECTRICAL / ENVIRONMENTAL		
Mechanical	Form Factor	2U rack mount chassis
	Color / Material	Black / Metal
	Dimensions	26" x 17.2" x 3.5" (660mm x 438mm x 87mm)
	Weight	30.86lb (14kg)
Electrical	Power Supply	800W Redundant
	Power Input	100 ~ 240V AC
Environmental	Operating Temperature	32°F to 122°F (0°C to 50°C)
	Storage Temperature	-40°F to 158°F (-40°C to 70°C)
	Operating Humidity	5% to 85% RH, non-condensing

Certification

* Weight is on chassis without HDDs *The latest product information / specification can be found at www.hanwhasecurity.com * Bandwidth performance figures based on performance testing by Hanwha Techwin using Wisenet WAVE

Unit: inch (mm) **Dimensions**

UL, cUL, CB, FCC, 80 Plus Platinum

